

SCS - SCS 200 - SCS 500 SCS 300 ABS - SCS 500 ABS



Compressori d'aria insonorizzati a pistone, avviamento diretto

Silent piston air compressors, DOL starter

SCS



Type	Cod.														
400/50/3 ■		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SCS 415	1688871000	-	400	14	24	10	145	3	2,2	AB 515	2/1	1210	68	837x592x735 32.6x23x28.6	115 254
SCS 540	1693282000	-	540	19	32,4	10	145	4	3	AB 598	2/2	1170	68	837x592x735 32.6x23x28.6	125 275
SCS 598	1693292000	-	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	69	837x592x735 32.6x23x28.6	160 353
SCS 958	1692942000	-	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	837x592x735 32.6x23x28.6	170 375
SCS 988	1684622000	-	910	32.2	54,6	10	145	10	7,5	AB 998	2/2	1070	66	837x592x735 32.6x23x28.6	170 375



SCS 200
SCS 300
SCS 500

Type	Cod.														
400/50/3 ■		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SCS 415/200	1686701000	200	400	14	24	10	145	3	2,2	AB 515	2/1	1210	68	837x592x735 32.6x23x28.6	175 386
SCS 540/300	1693632000	270	540	19	32,4	10	145	4	3	AB 598	2/2	1170	68	1440x592x1220 56.7x23x48	190 419
SCS 598/300	1693662000	270	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	69	1440x592x1220 56.7x23x48	215 474
SCS 958/300	1692932000	270	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	1440x592x1220 56.7x23x48	230 507
SCS 988/300	1720722000	270	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	1440x592x1220 56.7x23x48	230 507
SCS 958/500	1692922000	500	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	2000x600x1330 78.7x23.6x52.4	305 672
SCS 988/500	1686152000	500	910	32.2	54,6	10	145	10	7,5	AB 998	2/2	1070	66	2000x600x1330 78.7x23.6x52.4	305 672

SCS 300 ABS
SCS 500 ABS

Con essiccatore / With dryer (ABS)



Type	Cod.														
400/50/3 ■		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SCS 540/300 ABS	1693002000	270	540	19	32,4	10	145	4	3	AB 598	2/2	1170	68	1440x592x1220 56.7x23x48	230 507
SCS 598/300 ABS	1693012000	270	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	68	1440x592x1220 56.7x23x48	235 518
SCS 958/300 ABS	1692912000	270	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	1440x592x1220 56.7x23x48	275 606
SCS 988/300 ABS	1723042000	270	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	1440x592x1220 56.7x23x48	275 606
SCS 958/500 ABS	1692902000	500	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	2000x600x1330 78.7x23.6x52.4	340 750
SCS 988/500 ABS	1684112000	500	910	32.2	54,6	10	145	10	7,5	AB 998	2/2	1070	66	2000x600x1330 78.7x23.6x52.4	340 750

SSA - SSA 300 - SSA 500 SSA 300 ABS - SSA 500 ABS



Compressori d'aria insonorizzati a pistone, avviamento stella triangolo

Silent piston air compressors, star-delta starter

SSA



Type	Cod.											LxPxH			
400/50/3		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SSA 598	1701065000	-	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	65	837x592x735 32.6x23x28.6	120 264
SSA 958*	1701085000	-	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	65	837x592x735 32.6x23x28.6	187 412
SSA 998 *	1697795000	-	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	65	837x592x735 32.6x23x28.6	190 418.9

* Con controllo automatico livello olio / With automatic oil level control



SSA 300
SSA 500

Type	Cod.											LxPxH			
400/50/3 ○		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SSA 598/300	1704425000	270	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	66	1440x592x1220 56.7x23.3x48	215 474
SSA 958/300*	1698115000	270	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	1440x592x1220 56.7x23.3x48	247 544
SSA 998/300*	1723055000	270	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	1440x592x1220 56.7x23.3x48	250 551
SSA 598/500	1725655000	500	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	66	2000x600x1330 78.7x23.6x52.4	290 640
SSA 958/500*	1704445000	500	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	2000x600x1330 78.7x23.6x52.4	322 709.9
SSA 998/500*	1723075000	500	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	2000x600x1330 78.7x23.6x52.4	325 716.5

* Con controllo automatico livello olio / With automatic oil level control



SSA 300 ABS
SSA 500 ABS

Con essiccatore / With dryer (ABS)

Type	Cod.											LxPxH			
400/50/3 ○		ℓ	ℓ/min	CFM	m³/h	bar	psi	HP	kW	Grup. Pump	Cil. St.	min-1	dB (A)	mm in	kg lb
SSA 598/300 ABS	1725665100	270	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	66	1440x592x1220 56.7x23.3x48	235 518
SSA 958/300 ABS*	1697905100	270	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	1440x592x1220 56.7x23.3x48	267 588.6
SSA 998/300 ABS*	1723065100	270	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	1440x592x1220 56.7x23.3x48	270 595
SSA 598/500 ABS	1725445100	500	600	21.1	35,9	10	145	5,5	4	AB 598	2/2	1270	66	2000x600x1330 78.7x23.6x52.4	255 562
SSA 958/500 ABS*	1704465100	500	830	29.3	49,8	10	145	7,5	5,5	AB 998	2/2	980	66	2000x600x1330 78.7x23.6x52.4	342 754
SSA 998/500 ABS*	1723075100	500	1070	37.8	64,2	10	145	10	7,5	AB 998	2/2	1270	66	2000x600x1330 78.7x23.6x52.4	345 760.6

* Con controllo automatico livello olio / With automatic oil level control